

Redicote® E-4875 NPF

Emulsifier for cationic slow-setting emulsions suitable for tack, prime, slurry seal, cold mix and sealcoats

Benefits and features

- Low use level**
 0.8-1.2% is suitable for most applications
- Proven performance**
 Based on established formulation used in a wide range of applications
- Slurry seal**
 Plenty of mix time with the most reactive aggregates and at high temperatures
- Easy handling**
 Redicote E-4875 NPF has low viscosity and is completely water soluble
- Solvent-free dense-graded mixes**
 Good coating and extended workability in dense aggregate mixes, reclaimed materials or soils
- Does not contain NP Ethoxylates**

Storage and handling

Redicote E-4875 NPF may be stored in carbon or stainless steel tanks. Bulk storage should be maintained at 20-40°C (68-104°F). Redicote E-4875 NPF is alkaline and may cause severe irritation or burns to skin and eyes. Protective goggles and gloves must be worn when handling this product. For further information consult the Safety Data Sheet.

Packaging information

Redicote E-4875 NPF is available in bulk shipment, in plastic tight head drums of 210 kg (463 lbs) net weight, or in one-way totes (IBCs) of 1000 kg (2204 lbs).

Dosage

Cationic slow set emulsion	0.8-2.0%	pH 2-5 hydrochloric acid
----------------------------	----------	-----------------------------

Emulsion quality is improved by using 0.1-0.3% calcium chloride in the emulsion recipe

Specification

Active content, %	46-51	AB-46-1208
Total basic nitrogen, mmol/g	0.45-0.65	AB-46-1691

Physical properties

Appearance at 25°C	dark liquid
Flash point, °C	59 (138°F) ISO 2179 >100 (212°F) ISO 2592
Pour point, °C	<-5 (<41°F)

Density, g/cc at 20°C	1.07
Density, lbs/U.S. gal at 20°C	9.09
Viscosity, mPa.s (cP) at 20°C	1200

Physical properties are typical data based on our own measurements or derived from the literature. They do not constitute part of the delivery specification.

Contact us directly for detailed product information and sample request
website | nouryon.com/markets/asphalt
email | asphalt@nouryon.com

Nouryon

Nouryon is a global, specialty chemicals leader. Markets and consumers worldwide rely on our essential solutions to manufacture everyday products, such as personal care, cleaning goods, paints and coatings, agriculture and food, pharmaceuticals, and building products. Furthermore, the dedication of more than 7,900 employees with a shared commitment to our customers, business growth, safety, sustainability and innovation has resulted in a consistently strong financial performance. We operate in over 80 countries around the world with a portfolio of industry-leading brands. Visit our website and follow us @Nouryon and on LinkedIn.

All information concerning our products and/or all suggestions for handling and use contained herein (including formulation and toxicity information) are offered in good faith and are believed to be reliable. However, Nouryon makes no warranty express or implied (i) as to the accuracy or sufficiency of such information and/or suggestions, (ii) as to any product's merchantability or fitness for a particular use or (iii) that any suggested use (including use in any formulation) will not infringe any patent. Nothing contained herein shall be construed as granting or extending any license under any patent. The user must determine for itself by preliminary tests or otherwise the suitability of any product and of any information contained herein (including but not limited to formulation and toxicity information) for the user's purpose. The safety of any formulations described herein has not been established. The suitability and safety of a formulation should be confirmed in all respects by the user prior to use. The information contained herein supersedes all previously issued bulletins on the subject matter covered.

Products mentioned are trademarks of Nouryon and registered in many countries.

nouryon.com